



PT ADIKONS INDUSTRI PERKASA



Jl. Garuda No.19, Jakarta Pusat
Gading Park View

Jl. Boulevard Timur Blok ZD No.3
Jakarta Utara



Office 021 4586 0209
Mobile +62 818 973 125
Service +62 811 8866 266



sales@adikons.com



meiwa



Denyo

Fueling Progress Powering Innovations



YINENG





MEIWA SEISAKUSHO, LTD.

URL: <http://www.meiwa-ltd.co.jp>

Head Office:

18-2, Aoki 1-chome, Kawaguchi City, Saitama-Pref. 332-0031 Japan

Tel: 81-48-251-4525 Fax: 81-48-256-0409



TYPE MSR7M

Operating Weight	737 Kg
Shipping Weight	695 Kg
Overall Length	2410 mm
Overall Width	702 mm
Overall Height	1105 mm
Wheel Base	570 mm
Min. Road Clearance	170 mm
Drum Size	φ 406 × 650 mm
Compaction Width	650 mm
Vibration Frequency	55 (3300) Hz (vpm)
Centrifugal Force	20.0 (1400) kN (kgf)
Gradeability	25°
Water Tank Capacity	42 L
Engine	Kubota EA300 Diesel 7.0 PS
Fuel Tank Capacity / Diesel	4.8 L Diesel
Hydraulic Oil Capacity	10 L
Starting System	Electric Starter

TYPE RT70R

Operating Weight	70 Kg
Overall Length	700 mm
Overall Width	430 mm
Overall Height	1110 mm
Plate Size	330 x 270 mm
Impact Cycle	10 - 10.8 Hz
Impact Stroke	40 - 60 mm
Engine	Robin
Fuel Tank Capacity	2.5 L Gasoline

YINENG

YN939G WHEEL LOADER

Specification

Main

Operating Weight	10.600 Kg
Capacity Heaped ISO/SAE	1.8 - 2.0 M3
Rated Load	3000 Kg
Max. Drawing Force (Traction)	96 kN
Max. Breakout Force (Digging)	120 kN
Max. Gradeability	30 Degree
Dumping Height (at Fully Raised)	3000 mm
Dumping Reach (at Fully Raised)	1100 mm
Overall Dimension	6910 x 2510 x 3230 mm

Engine

Model	Weichai Deutz WP6G125E23 Tier II Mechanical Engine
Type	Turbo, Direct Injection
No. of Cylinder	6
Max. Torque	500 Nm / 1400 - 1500 rpm
Rated Power	92 kW / 2200 rpm

Transmission System

Torque Converter	Four Elements Double Turbine Hydraulic
Transmission	Hangzhou YX936
Gear Shift	2 Forward, 1 Reverse
Max. Travel Speed	36 Km/h

Operation

Total Cycle	10 Sec
Boom Lifting Time	5.5 Sec



Axles and Chassis

Axles	Planetary-Type Hub Drive
Chassis	Heavy Duty for 4-ton Class Loader
Wheelbase	2700 mm
Wheel Tread	1865 mm
Tyre Specification	17.5 - 25 12 PR

Steering and Control

Steering System	Fully Hydraulic Load Sensing
Steering Angle	36°
Control Type	Single Lever Joystick Pilot Control
Min Turning Radius (outside tyres)	5160 mm
Min Ground Clearance	375 mm
Cabin	Air-Conditioned with Integral Instrument Board

Others

Brakes System	Air over hydraulic disks on four wheel brakes
Joints	Double sealed hydraulic pipeline joints
Bucket Articulated Points	Sealed, lubricated, Dust-proof layers
Hydraulic System	Single Pump, Split Flow



PT ADIKONS INDUSTRI PERKASA

Jl Boulevard Timur Blok ZD No.3
Kelapa Gading Jakarta Utara, 14250
Telp. : (021) 4586 0209/19
Fax. : (021) 4586 0220
Email : sales@adikons.com

Salesman :